Progress and Findings of the Decomp(artmentalzation) Physical Model



West Palm Beach, FL. March 1, 2016

Colin Saunders South Florida Water Management District













DPM Science Team



F. Sklar

C. Saunders

M. Manna

E. Clilne

S. Newman

C. Hansen

C. Coronado

M. Blaha

C. Zweig

F. Santarmaria

E. Tate-Boldt



US Army Corps of Engineers

S. Baisden

S. Wilcox

N. Garratt

D. Crawford



L. Larsen

D. Watts

J. Trexler

M. Bush

S. Bornhoeft

M. Ross

P. Ruiz

R. Jaffe

D. He

P. Regier

J. Sah





J. Harvey

B. Rosen

M. Dickman

Jay Choi

J. Lewis

A. Swartz

J. Gomez

K. Skalak



D. Ho

D. Hickman




Restoration: What is the ecological function of sheetflow and what are the hydrologic needs (i.e., flow fields, depths, duration) of the ridge and slough landscape?

<u>Sediment</u>: What is the role of floc and sediment movement for restoring and sustaining a stable ridge and slough landscape? What are the impacts on biogeochemical cycling?

<u>Backfilling</u>: how do canals, levees, and levee modifications affect sediment movement? Fish populations?

Sheetflow Hypothesis Cluster

Deep water sloughs exhibit higher velocities, more sediment transport High-flow redistributes sediment from sloughs into ridges




Canal Backfill Hypothesis Cluster

Is canal backfilling needed to maintain sediment transport?

Does backfilling prevent downstream nutrient loading?

Does backfilling impact fish populations?


















DPM Experimental Design



















DPM Experimental Design

Construction


- L67A: ten 6-ft gated culverts
- L67C: 3000-ft gap and 3 canal-backfill treatments

BACI design

- 11 marsh sites
- 5 canal sites
- Before-, Impact- sampling

S-152 Operational constraints

- Flooding in WCA3B
- Water quality in L67A
- Operational window is November-January


















Flow field resolved with water tracers



Dye tracer, 2013










Flow Effects on Sediment Transport – Horizontal Traps


- adapted from Phillips et al., 2000 Hydrol Procs.
- Mid-water column, parallel to flow
- Deployed at spatial sites
- Nov-Jan 2012, 2013, 2014, 2015 ...





Flow Effects on Sediment Transport – Horizontal Traps

- adapted from Phillips et al., 2000 Hydrol Procs.
- Mid-water column, parallel to flow
- Deployed at spatial sites
- Nov-Jan 2012, 2013, 2014, 2015 ...




Distance from S-152 (m)

Data from C. Saunders, SFWMD






Benefits of Sustained Discharges – Slough Velocities Increase




Data from Jud Harvey, Jay Choi and Mark Dickman, USGS

Sediment Transport RAMPS UP with sustained flow

- BACI sampling
- C1, RS1, RS2
- ridge & slough
- 3-wk Oct-Jan,6-wk Feb-April
- 2011, 2012, 2013, 2014





SOUTH FLORIDA WATER MANAGEMENT DISTRICT

















Slough Floc Reduced Under Sustained Flow



















Slough Floc Reduced Under Sustained Flow



Pre-Flow Flow #1 Floc Height (cm) Flow #2 Flow #3 -10 Weeks After Flow Starts

Data from C. Saunders - SFWMD

Paq – Biomarker for Slough vs Ridge Organic Matter



R. Jaffe, D. He (FIU)

















Paq is a ratio of fatty acid chain lengths – higher values (>0.4) correspond to slough derived OM (vascular plants only), lower values (<0.3) are ridge-derived</p>

R. Jaffe, D. He (FIU)














The Initial Pulse - Tracking Phosphorus and Sediment Across the Landscape









S. Newman, E. Tate-Boldt, C. Hansen, Christa Zweig (SFWMD)














Lessons Learned (Water Quality)

Stopping flow appeared to raise TP concentrations



Data from Newman, Cline, Tate-Boldt and Hansen






















- Canal velocimeters
- Dye tracers
- Vertical sediment traps
- Molecular Biomarkers
- Sediment Chemistry (CNP, LOI)























Monitoring Large Fish in L67C Canal





- Starting in 2010, CPUE monitored five times per year
- Electrofishing catch per 5-min.
- Initial sampling focused on canal edges (vegetated littoral zone) fish seldom observed in canal center
















- After construction (started Jan 2013) sampling started in canal center
- Partial & Complete Fill areas attained similar CPUE to canal edges
- Backfill treatments have created more high-quality fish habitat by increasing vegetated areas similar to canal edges



Data from J.Trexler (FIU)



































Paq – Slough Macrophyte Indicator







Data from R. Jaffe, P. Regier, and D. He (FIU)













Sediment TP (Marsh vs Canal)

- Phosphorus content highest in canal sediments
- Suggests canal accumulating a local source of sediment
- Canals a potential source of P



Data from L. Larsen (UCB), Coronado (SFWMD) and Saunders (SFWMD) *L-28 Merkel & Hickey-Vargas 2000. Water, Air, and Soil Pollution





Data from J. Trexler (FIU), J.Harvey (USGS), C.Coronado (SFWMD), E.Cline (SFWMD)















Canal Sediment Accumulation under High Flow (g m⁻² d⁻¹)



- Re-routing of flow down the canal
- Sediments concentrate and settle at the No-Fill site
- This creates a "hotspot" of sediment accumulation


Data from C. Coronado-Molina (SFWMD)





Lessons Learned (Operational)

- 1. The interagency operations team proved flexible to adapt to anomalous years like this last flow event. Rapid communication within and among agencies was critical for managing for a strong El Nino, changing operations and adding a new trigger.
- Having a rich data set (15 years) and especially weekly data in the last 3 years proved essential to operational decisions.
- 3. This year's data should be helpful for determining how operations (for future DPM studies, and ultimately CEPP) that extend beyond January (the current limit for DPM).
- 4. The DPM structure will benefit general operations and the management of high water conditions in 3A (e.g., Emergency Orders).















- Achieved velocities high enough to erode and redistribute sediments from ridge to slough
- Operations:
 - (1) Initial pulses increase sediment transport 10-fold
 - (2) Sustained flows (10+ weeks) increase slough velocities, reduce slough floc and change floc properties
- Water does not follow the historic flowpath and high velocities are limited to 500-m downstream. Active management may help ... and ...
- The impacts of flow on biogeochemical cycling in algae and floc are being observed further downstream each year















Conclusions - Effects of Flow & Backfilling on Canal Sediment Dynamics

- Backfill treatments improve habitat for large fish, but recovery from disturbance is ongoing
- Flow affected all canal sites due to radial, eastward flow, mobilizing sediments from the canal edge or the canal itself
- Re-routing of flow and sediments down the canal creates a "hotspot" of high-P sediment accumulation and preferential flow in the No-Fill area
- Backfill treatments reduce sediment TP, but they are still recovering from disturbance and re-vegetation

